



TD4 Benchtop Low Speed Centrifuge

TD4 benchtop low speed centrifuge can be widely used in small hospitals, biochemical laboratories and beauty salons. With compact footprint and user-friendly touch screen, to enable fast centrifugation. It is a must-have equipment for sample separation.

Product advantages

- ◆ Microprocessor control, DC brushless motor for stable and low noise operation.
- ◆ Parameters can be set freely during a run.
- ◆ Countdown time showed by seconds if the centrifugation time is less than 1min.
- ◆ Self-diagnosis system can automatically detect the faults of over-speed and no speed signal, door lid interlock to improve the safety performance.
- ◆ Compact with great performance.
- ◆ Special damping structure to reduce vibration and noise.
- ◆ 5 inch HD touch screen, simple interface, setting parameters and running parameters at a glance.

Technical parameter

Order NO	0205194000
Max Speed	4000r/min
Max RCF	1980xg
Max Capacity	8×15ml
Speed Accuracy	±30r/min
Time Setting Range	1min~99min
Noise	≤ 62dB (A)
Power Supply	AC 220±22V 50/60Hz
Power Consumption	100W
Dimension (WxDxH)	320×370×235(mm)
Packing Dimension (WxDxH)	530×410×290(mm)
Net Weight	11kg

Rotor parameters



Rotor Type: Angle Rotor
 Max Speed: 4000r/min
 Max RCF: 1980xg
 Max Capacity: 8x15ml
 Order NO: 0301809030

